



HEVEA MATS

HeveaMats ApS
Adresse: Tirslundvej 34, 6650 Brørup
Tlf: +45 61669044
Email: info@HeveaMats.dk
Web: www.HeveaMats.dk

Datablad Natural Supreme 42

Dansk

Anvendelse	Legepladsen, haven, terrassen, altanen, fodboldbanen osv.
------------	-----------------------------------------------------------

Fiber	Polyethylen og polypropylen
-------	-----------------------------

Antal fiber	13.100 Dtex
Produktionsmetode	Tufted - 5/8"
Primær baggrund	100% Polypropylen m. fiberlås fleece
Sekundær baggrund	SBR-gummi; ca. 760 gr/m ²
Strå	11.340 /m ² (+/- 10%)
Højde strå	42 mm. (+/- 10%)
Total højde strå	44 mm. (+/- 10%)
Strå vægt	1.495 g/m ² (+/- 10%)
Total vægt	2.415 g/m ² (+/- 10%)

Fyld	Sand (> 80% rund), 5-10 kg/m ²
------	-------------------------------------------

Rulle bredde	200 cm eller 400 cm
Rulle længde	I henhold til lay-out

Farve	Grøn
-------	------

UV-stabilitet	> 6000 timer
Vandpermeabilitet	60 liter/min/ m ²

Engelsk

Employment	The playground, the garden, the terrace, the balcony, the football pitch, etc.
------------	--------------------------------------------------------------------------------

Fibre	Polyethylene and Polypropylene
-------	--------------------------------

Yarn Detex	13.100 Dtex / 16 ply
Production method	Tufted - 5/8"
Primary backing	100 % PP with fibre-lock fleece
Secondary backing	SBR Latex; aprox 760 gr/m ²
Stitches	11.340 /m ² (+/- 10%)
Pile height	42 mm. (+/- 10%)
Total height	44 mm. (+/- 10%)
Pile weight	1.495 gr / m ² (+/- 10%)
Total weight	2.415 gr / m ² (+/- 10%)

Infill	Sand (> 80% round), 5-10 kg/m ²
--------	--------------------------------------------

Roll Width	200 or 400 cm
Roll Length	As per lay-out

Colour	Green
--------	-------

UV-Stability	> 6.000 hours
Water Permeability	60 liter/min/ m ²